


Cybersource Verification Services

Using the Simple Order API

October 2020



cybersource
A Visa Solution

Cybersource Contact Information

For general information about our company, products, and services, go to <http://www.Cybersource.com>.

For sales questions about any Cybersource Service, email sales@Cybersource.com or call 650-432-7350 or 888-330-2300 (toll free in the United States).

For support information about any Cybersource Service, visit the Support Center at <http://www.Cybersource.com/support>.

Copyright

© 2020 Cybersource Corporation. All rights reserved. Cybersource Corporation ("Cybersource") furnishes this document and the software described in this document under the applicable agreement between the reader of this document ("You") and Cybersource ("Agreement"). You may use this document and/or software only in accordance with the terms of the Agreement. Except as expressly set forth in the Agreement, the information contained in this document is subject to change without notice and therefore should not be interpreted in any way as a guarantee or warranty by Cybersource. Cybersource assumes no responsibility or liability for any errors that may appear in this document. The copyrighted software that accompanies this document is licensed to You for use only in strict accordance with the Agreement. You should read the Agreement carefully before using the software. Except as permitted by the Agreement, You may not reproduce any part of this document, store this document in a retrieval system, or transmit this document, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written consent of Cybersource.

Restricted Rights Legends

For Government or defense agencies. Use, duplication, or disclosure by the Government or defense agencies is subject to restrictions as set forth the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 and in similar clauses in the FAR and NASA FAR Supplement.

For civilian agencies. Use, reproduction, or disclosure is subject to restrictions set forth in subparagraphs (a) through (d) of the Commercial Computer Software Restricted Rights clause at 52.227-19 and the limitations set forth in Cybersource Corporation's standard commercial agreement for this software. Unpublished rights reserved under the copyright laws of the United States.

Trademarks

Authorize.Net, eCheck.Net, and The Power of Payment are registered trademarks of Cybersource Corporation.

Cybersource, Cybersource Payment Manager, Cybersource Risk Manager, Cybersource Decision Manager, and Cybersource Connect are trademarks and/or service marks of Cybersource Corporation.

All other brands and product names are trademarks or registered trademarks of their respective owners.

Contents

Recent Revisions to This Document 6

About This Guide 7

Audience and Purpose 7

Scope 7

Conventions 8

 Note and Important Statements 8

 Text and Command Conventions 8

Related Documents 9

Customer Support 9

Chapter 1 Introducing Verification Services 10

Delivery Address Verification 10

 Address Validation 11

 Address Standardization 12

 Countries Supported by Delivery Address Verification 12

 Status and Error Codes 12

Export Compliance 13

Chapter 2 Integrating Verification Services into Your Business 14

Requesting Delivery Address Verification 14

 Interpreting the Delivery Address Verification Reply 15

 Returned Reply Fields 15

Requesting Export Compliance 17

 Handling the Results of Denied Parties List Checks 17

 Excluding Export Compliance Results 18

 Configuring Denied Parties List Matches 19

 Adjusting Name and Address Word Matching 20

 Defining Name and Address Matching Rules 20

Chapter 3	Testing Verification Services	22
	Requirements for Testing	22
	Testing Export Compliance	23

Appendix A	API Fields	25
	Formatting Restrictions	25
	Data Type Definitions	25
	Numbered Elements	26
	Request Fields	27
	Reply Fields	34

Appendix B	Reason Codes	39
-------------------	---------------------	-----------

Appendix C	Status and Error Codes	42
	Status Codes: U.S. Addresses	42
	Status Codes: International Addresses	46
	Error Codes: U.S. Addresses	49
	Error Codes: International Addresses	50

Appendix D	Request and Reply Examples	52
	Delivery Address Verification Examples	52
	Name-Value Pair Request	52
	Name-Value Pair Reply	53
	XML Request	53
	XML Reply	55
	Export Compliance Examples	56
	Example of Declined Transactions	56
	Name-Value Pair Request	56
	Name-Value Pair Reply	56
	XML Request	57
	XML Reply	58
	Name and Address Word Matching Examples	58
	Name-Value Pair Request	59
	Name-Value Pair Reply	59
	XML Request	60
	XML Reply	60
	Name and Address Matching Rule Examples	61

[Name-Value Pair Request](#) 61

[XML Request](#) 62

Appendix E [Export Compliance Standard Codes](#) 63

[Denied Parties List Check Codes](#) 63

[Product Codes](#) 65

Appendix F [Country or Region and Territory Postal System Categories](#) 66

[Category I-A](#) 66

[Category I-B](#) 67

[Category II](#) 67

[Category III](#) 68

[Category IV](#) 69

Appendix G [Restricted and Denied Parties List](#) 75

Appendix H [Address Type](#) 80

Recent Revisions to This Document

Release	Changes
October 2020	This revision contains only editorial changes and no technical updates.
July 2020	Updated Appendix G, " Restricted and Denied Parties List ," page 68 . Fixed some links in Preface and corrected 2 country abbreviations. For Simple Order only, added the endpoint for transactions in India.
October 2019	This revision contains only editorial changes and no technical updates.
January 2018	<ul style="list-style-type: none"> ■ Added information about the Cybersource APIs to the Cybersource web site. See the Cybersource API Versions page. ■ Added "Numbered Elements," page 26. ■ Updated descriptions for the item-level request fields. See "Request Fields," page 26.
September 2017	<ul style="list-style-type: none"> ■ Updated Export Compliance to include support for more government agency lists. See "Handling the Results of Denied Parties List Checks," page 17. ■ Revised the <code>billTo_state</code> field description to clarify that the field is only required if the value is CA or US. See billTo_state, page 27. ■ Added the <code>exportService_sanctionsLists</code> API request field. See exportService_sanctionsLists, page 30. ■ Added new international lists to the "Restricted and Denied Parties List," page 68.
August 2017	<ul style="list-style-type: none"> ■ Added details for testing Export Compliance. See "Requirements for Testing," page 22. ■ Updated <code>billTo_company</code>, <code>billTo_firstName</code>, and <code>billTo_lastName</code> fields to clarify that first name and last name or company name fields must be submitted. ■ Updated Export Compliance samples. See "Request and Reply Examples," page 52.
April 2016	<ul style="list-style-type: none"> ■ Added note that Verification Services do not support relaxed requirements for address data. See "Integrating Verification Services into Your Business," page 14. ■ Updated URL for testing. See "Requirements for Testing," page 22.

About This Guide

Audience and Purpose

This guide is written for application developers who want to use the Cybersource Simple Order API to integrate address verification or export compliance verification services into their order management system.

Implementing Cybersource Verification Services requires software development skills. You must write code that uses the API request and reply fields to integrate Verification Services into your existing order management system.

Scope

This guide describes only the tasks and API fields you must use to integrate Verification Services into your order management system. It does not describe how to integrate other Cybersource services. For that information, see "[Related Documents](#)," page 9.

Conventions

Note and Important Statements



Note

A *Note* contains helpful suggestions or references to material not contained in this document.



Important

An *Important* statement contains information essential to successfully completing a task or learning a concept.

Text and Command Conventions

Conventions	Usage
bold	<ul style="list-style-type: none"> Field and service names; for example: Include the ics_applications field. Items that you are instructed to act upon; for example: Click Save.
<i>italic</i>	<ul style="list-style-type: none"> Filenames and pathnames. For example: Add the filter definition and mapping to your <i>web.xml</i> file. Placeholder variables for which you supply particular values.
Screen text	<ul style="list-style-type: none"> XML elements. Code examples and samples. Text that you enter in an API environment; for example: Set the davService_run field to <code>true</code>.

Related Documents

- *Getting Started with Cybersource Advanced for the Simple Order API* describes how to get started using the Simple Order API. ([PDF](#) | [HTML](#))
- *Decision Manager Using the Simple Order API Developer Guide* describes how to integrate Decision Manager, a fraud detection service, with your order management system. ([PDF](#) | [HTML](#))
- *Credit Card Services Using the Simple Order API* describes how to integrate Cybersource payment processing services into your business. ([PDF](#) | [HTML](#))
- *Business Center Reporting User Guide* describes how to view and configure Business Center reports. ([PDF](#) | [HTML](#))
- The [Cybersource API Versions page](#) provides information about the Cybersource API versions.

Refer to the Support Center for complete Cybersource technical documentation:

<http://www.Cybersource.com/en-us/support/technical-documentation.html>

Customer Support

For support information about any Cybersource service, visit the Support Center:

<http://www.Cybersource.com/support>

Introducing Verification Services

Cybersource Verification Services are part of a suite of services that include electronic payment and fraud management. Verification Services consist of two services:

- Delivery Address Verification
- Export Compliance

**Note**

You are responsible for creating your order acceptance strategy. If you do not have the expertise, you are also responsible for seeking expert help outside of your company. Cybersource cannot make recommendations for your business.

Delivery Address Verification

Delivery Address Verification verifies a customer's delivery address during card-not-present transactions, and then it returns a result. The result contains an API-specific reply code and a status or error code that is specific to the results of address verification. Verification tests produce a valid address and an estimate of the risk associated with the address. As a result, your shipping and customer service costs caused by address errors can be reduced.

The verification process consists of *validation* and *standardization* of submitted addresses. After a customer provides address information to your system, you send the address in a request to Cybersource for verification.

When Cybersource Verification Services receives the address information in your request, the address is validated and standardized as described in the following sections.

Address Validation

During validation, address information is corrected. For example, the following items are verified:

- The street number must be valid for the street.
- The street name must be valid for the city.
- The postal code must be valid for the city.

If the postal code in the submitted address is valid, it is used to determine the city and state or province.

Example 1 Customer-Submitted Address Information

A customer submits the following address information to your system while placing an order:

44 Fisher Street
Mtn View, Florida
94043

The address information submitted by the customer contains several errors that can be corrected by Verification Services as described in the following table:

Table 1 Address Validation

Submitted Information	Problem	Corrected Address
44 Fisher Street	Street number is invalid.	34 Fisher Street
Mtn View	The first word of the city name is abbreviated by using a non-standard abbreviation, so it is considered misspelled.	Mountain View
Mtn View, Florida 94043	The city and state do not match the postal code.	Mountain View, California 94043

Address Standardization

During standardization, address information is arranged in a consistent, preferred format by using common abbreviations. For example:

- *DEPT* is used for department
- *St* for Street
- *SW* for Southwest

After the address information submitted by the customer in [Example 1](#) is validated, the address is standardized as follows:

Table 2 Address Standardization

Submitted Information	Problem	Corrected Address
34 Fisher Street Mountain View, California 94043	The street and state names are abbreviated using common abbreviations.	34 Fisher St Mountain View, CA 94043

Countries Supported by Delivery Address Verification

Delivery Address Verification uses data from postal service databases, updated monthly from over 200 countries and territories. See [Appendix F, "Country or Region and Territory Postal System Categories,"](#) on page 59.

Status and Error Codes

Cybersource returns information codes for each address when address verification is attempted. These codes can include an API-specific reply code and a status or error code that describe the degree of match or reasons for the failure to match. When you have integrated Verification Services into your business, your system interprets the reply codes according to your business rules. Address verification failure rates depend on the address location and the category of the country, region, or territory as listed in [Appendix F, "Country or Region and Territory Postal System Categories,"](#) on page 59. An address that requires correction is not considered a failure.

Address verification returns one of these results:

- Address requires *no correction*. You receive the appropriate success information code.
- Address requires correction. You receive an API-specific reply code and a status code that describe the type of correction that is applied.

- Address cannot be verified. You receive an API-specific failure code and an error code that describe the type of failure.

For more information about API-specific reason codes, see "[Reason Codes](#)," page 39. For more information about address verification status and error codes, see "[Status and Error Codes](#)," page 41.

Export Compliance

Export Compliance enables you to comply with U.S. Export Administration Regulations, as well as internationally supported sanctions lists, which place restrictions on those with whom you can conduct business. The service verifies customer information and returns detailed information about declined orders.

Export Compliance checks customer information by comparing it to many lists that are maintained by government agencies to support export controls. If a customer's first name and last name or company name appears on any of the lists, you receive information indicating that the transaction is declined. You also receive a description of how the names match a list entry. For more information, see "[Restricted and Denied Parties List](#)," page 68.

You can use Export Compliance to manage your international sales territories by listing the allowed and disallowed export countries in each offer. A first name and last name or company name can be matched more than once to a list when different spellings or aliases exist. Although only some of these matches appear in the Business Center, all matches appear in the API reply.

If you use Decision Manager, you can create custom rules based on information codes, name matches, and export programs. In addition, you can create profile selector rules based on a name and address match. For more information, see the *Decision Manager User Guide* ([PDF](#) | [HTML](#)).

Integrating Verification Services into Your Business

For request and reply examples, see ["Request and Reply Examples," page 52](#).



- When requesting these services, be sure to send only valid and well-formed data in all fields, especially in the credit card account number, billing address, email address, and IP address fields.
- To use these services, you must collect the full address from your customers; Verification Services do not support relaxed requirements for address data.
- Cybersource supports multi-byte characters for all services except Delivery Address Verification, Stored Value, and Customer Profiles. Before implementing any of these services, contact your Cybersource representative to clarify any questions you have about multi-byte character support.

Requesting Delivery Address Verification

To request the address verification service, set the **davService_run** field to `true`. When requesting **davService**, do not request the following services:

- Authorization Reversal (**ccAuthReversalService**). For more information about this service, see *Credit Card Services Using the Simple Order API* ([PDF](#) | [HTML](#)).
- Risk Update (**riskUpdateService**). For more information about this service, see *Decision Manager Developer Guide Using the Simple Order API* ([PDF](#) | [HTML](#)).

To ignore the result of the address verification request so that the results do not prevent other services from functioning, use the **businessRules_ignoreDAVResult** request field. For descriptions of the request fields you can use, see ["API Fields," page 25](#).

Interpreting the Delivery Address Verification Reply

If Delivery Address Verification finds a match for the street address, it returns a corrected and standardized address. If you have used the **businessRules_ignoreDAVResult** request field, only a standardized address is returned. The standardized address is divided into separate fields for the street address, city, state, province, territory, and postal code. For descriptions of all the reply fields, see ["API Fields," page 25](#). For examples, see ["Request and Reply Examples," page 52](#).

Returned Reply Fields

The reply contains the standardized address in the reply fields that begin with **davReply_standardized**.

If you do not use the **businessRules_ignoreDAVResult** request field but want to know whether the address is correct, use the **davReply_reasonCode** field to get the address verification result.

Address verification is returned in the **davReply_addressType** field if the address can be normalized. If the request contains both the shipping and billing addresses, the reply contains information about the shipping address only. To obtain the most comprehensive address verification information, Cybersource recommends that you send separate requests for the billing address and the shipping address.

Status and Error Codes

For each verified address, you receive a status or an error code. *Status codes* contain information about corrections or standardizations that are applied to the address. *Error codes* contain information that explains why an address cannot be verified. Status and error codes are returned in the following reply fields:

Table 3 Status and Error Code API Reply Fields

Status Codes	Error Codes
davReply_usInfo	davReply_usErrorInfo
davReply_caInfo	davReply_caErrorInfo
davReply_intlInfo	davReply_intlErrorInfo

For a complete list of the status and error codes that can be returned in reply fields, see ["Status and Error Codes," page 41](#).

Example 2 Status Code Example

Each digit in the status code means something. If you receive `davReply_usInfo=S80000` in the reply from Cybersource, each digit in the code is interpreted as follows:

Table 4 Status Code Interpretation

Digit	Value	Interpretation
1st	S	Nothing truncated.
2nd	8	Assigned a different ZIP+4.
3rd	0	With primary name, directionals, and suffix, no significant difference between input and corrected data.
4th	0	With country number, CART (carrier-route number), DPBC (delivery point barcode), and unit designator, no significant difference between input and corrected data.
5th	0	No meaning is currently assigned to the 5th and 6th digits. They are reserved for future use.
6th	0	

Example 3 Error Code Example

All error codes start with the letter E and contain a 3-digit number, which indicates one specific type of error. You do not interpret each individual digit for error codes. For example, if you receive `davReply_usErrorInfo=E101` in the reply from Cybersource, the city, state, or ZIP code is invalid or missing.

**Note**

For international addresses, you might receive a successful reply (`reasonCode=100`) that contains an error code. You are responsible for determining the level of risk for such an address match. Review these addresses carefully before making a final decision on the order.

Information Codes

If you use the Advanced Fraud Screen scoring service in the same request, and the normalized address appears to be risky, a `RISK-AVS` information code is returned. This code means that the combined AVS (Address Verification Service) test result and the normalized billing address are risky. For example, a risky address may be one in which the AVS result indicates an exact match, but the normalized billing address is not deliverable. All information codes are listed in the “Information and Reply Codes” appendix of the *Decision Manager Developer Guide Using the Simple Order API* ([PDF](#) | [HTML](#)).

Requesting Export Compliance

To request Export Compliance, set the **exportService_run** field to `true`. For a list of the fields to use when you request the service, see ["Request and Reply Examples," page 52](#).

Do not request the following services at the same time that you request Export Compliance:

- Authorization Reversal (**ccAuthReversalService**). For more information about this service, see *Credit Card Services Using the Simple Order API* ([PDF](#) | [HTML](#)).
- Risk Update (**riskUpdateService**). For more information about this service, see the *Decision Manager Developer Guide Using the Simple Order API* ([PDF](#) | [HTML](#)).

To list the allowed and disallowed countries for each offer, use the fields **item_#_export** and **item_#_noExport**.



Note

Users can optionally send in an IP address, and Export Compliance can verify the IP country against the lists selected.

Handling the Results of Denied Parties List Checks

Countries with which U.S. trade is restricted are automatically checked during denied parties checks. You can also check other government agency lists as best fits your business needs. See the **exportService_sanctionsLists** request field and ["Restricted and Denied Parties List," page 68](#) for further details.

If a customer's name and address strongly correlates with an entry in a Denied Parties List (DPL), the following information is returned in the reply from Cybersource:

- Reason code 700
Because you always receive this flag for blocked countries, all customers from these countries receive this reason code.
- Reply fields starting with the **deniedPartiesMatch_** prefix describe the denied parties check correlation in more detail. You can receive an unlimited number of matches to names, addresses, and programs within the lists.



Note

The denied parties lists are watch lists that are maintained by government entities, such as the U.S. Treasury Department or the Australia Department of Foreign Affairs and Trade.

The following example shows a reply in which the order data matched two denied parties lists:

- In the first list (`Match_0`), the order matched 3 sub lists: programs 1, 2, and 3.
- In the second list (`Match_1`), the order matched 2 sub lists: programs 1 and 2.

Example 4 Denied Parties List Check Reply Example

```
deniedPartiesMatch_0_list=Bureau Of Industry and Security
deniedPartiesMatch_0_program_1=BXA_UNV
deniedPartiesMatch_0_program2=US_DEBARRED
deniedPartiesMatch_0_program_3=BXA_ENT
deniedPartiesMatch_1_list=Office of Foreign Assets Control
deniedPartiesMatch_1_program_1=SDNTK
deniedPartiesMatch_1_program_2=JADE
```

If you use Decision Manager, your custom rules that use `Export match program` as the order element return all result values delimited with carets (^) in the `deniedPartiesMatch_N_program_N` field. In the preceding example, the values are:

```
BXA_UNV^US_DEBARRED^BXA_ENT^SDNTK^JADE
```

The complete matched data is also available in the Case Details window.

Excluding Export Compliance Results

You can allow processing to continue regardless of the Export Compliance results by using the `businessRules_ignoreExportResult` request field. If you use this field, be sure to review all orders that fail Export Compliance.

When a transaction is declined by the DPL check or the export service, reason code 100 is returned for the transaction. In addition, the `exportReply_infoCode` field is returned containing one or more information codes. Other services in the request are processed normally.



If you use Decision Manager, you can create custom rules and profile selector rules that use the information codes that you receive from Export Compliance. These rules enable you to route different types of orders to specific review queues in your order management system. If you subscribe to Enhanced Case Management and want to view the export information results in the Case Details window of the Business Center, you must use the `businessRules_ignoreExportResult` field.

Example 5 Request and Reply Example that Uses the `businessRules_ignoreExportResult` Field

The following request example shows the international data that is used by Export Compliance and the use of the `businessRules_ignoreExportResult` field:

```
billTo_street1=26 JALAN MT. ERSKINE
billTo_city=PENANG
billTo_country=MY
billTo_hostname=www.Cybersource.ir
exportService_run=true
businessRules_ignoreExportResult=true
shipTo_street1=26 JALAN MT. ERSKINE
shipTo_city=PENANG
shipTo_country=be
```

The following reply shows that Export Compliance was processed successfully (`reasonCode=100`). However, three information codes were returned for the shipping address, the host name, and the Denied Parties List check:

```
exportReply_infoCode=MATCH-SCO^MATCH-HCO^MATCH-DPC
exportReply_ipCountryConfidence=99
deniedPartiesMatch_0_address_0=26 JALAN MT. 1 ERSKINE, PENANG, MY,
deniedPartiesMatch_0_list=Bureau Of Industry and Security
decision=ACCEPT
reasonCode=100
exportReply_reasonCode=100
```

Configuring Denied Parties List Matches

By default, Export Compliance searches for an exact match between a DPL and the information in the request. However, you can adjust the parameters that control what is required for a match by using the following order elements:

- **Name**
Export Compliance requires at least the name of the customer or the company name.
- **Address**
You can search by name *and* address. Provide as much information as possible to reduce the number of false positives returned in the results.

A false positive result occurs when a DPL contains information that is common to several individuals. For example, many people have the same first name, the same last name, or even the same first and last name. However, it is unlikely that individuals have the same first name, last name, company name, and address, especially if all of the information is complete.

Adjusting Name and Address Word Matching

You can specify how closely a customer's name, company name, or address must match by using these optional request fields:

- **exportService_addressWeight**
- **exportService_companyWeight**
- **exportService_nameWeight**

These fields can be set to `exact`, `high`, `medium`, or `low` to indicate how much the value in the order can deviate from an entry in a DPL. For example, if you set **exportService_nameWeight** to `medium`, and the customer's name does not differ significantly from an entry in a DPL, **exportService** detects a match. If you do not include these fields with your request, Export Compliance searches for an exact match only. For usage examples of these fields, see "[Request and Reply Examples](#)," page 52.

Defining Name and Address Matching Rules



To accurately match customer and company names with entries on a DPL, you must send names in the correct API field (**billTo_firstName**, **billTo_lastName**, and **billTo_company**).

Use the **exportService_addressOperator** field to specify how Export Compliance detects name and address matches. You can set this request field to one of the following values:

- AND (the default setting)



Although this is the default setting for the **exportService_addressOperator** field, you are responsible for ensuring that this setting provides accurate and appropriate results for your business.

Export Compliance detects a match only if both the name *and* the address match an entry in a DPL. Name can be the customer's name or the company name. Export Compliance evaluates all combinations available in the request:

- Name and billing address
- Name and shipping address
- Company and billing address
- Company and either shipping address, blocked billing, or blocked shipping country

However, if a request contains only a name, the `AND` setting matches the name with any address. Add all available address elements to receive the most accurate match and the fewest false positives. For more information about the behavior of this setting, see ["Interactions between Match Weight and the AND Matching Rule."](#)

- `OR`
Export Compliance detects a match if the customer's first name, last name, or company name match an entry on a DPL. An address cannot trigger a DPL match on its own.
- `IGNORE`
Export Compliance detects a match based on only the customer's name or the company name and ignores the address. However, the blocked countries check is still performed.

[Interactions between Match Weight and the AND Matching Rule](#)

When the `exportService_addressOperator` field is set to `AND`, a combination of customer or company name *and* address is checked. All possible combinations are evaluated before the DPL check results are returned. The match weight level specified for the customer name or the company name (`exportService_nameWeight` and `exportService_companyWeight`) is used for all order elements in the request.

Therefore, if you set name and company to different weights, and send a request that contains a customer name, a company name, and an address, each pair of values is evaluated independently.

Example 6 Export Compliance Evaluation Example

A request includes the following:

- First and last name with the name weight set to high (`exportService_nameWeight=high`)
- Company name with the company weight set to low (`exportService_companyWeight=low`)

Export Compliance evaluates the request as follows:

- A high weight is set on the combination of customer name and address. The customer name and address *cannot* differ significantly from an entry in a DPL to register a match.
- A low weight is set on the combination of company name and address. The company name and address *can* differ significantly from an entry in a DPL to register a match.

Testing Verification Services

To ensure that your requests are processed correctly, you must test the basic success and error conditions for each Cybersource service you plan to use.

Requirements for Testing

- Use your regular Cybersource merchant ID when you are testing your system.
- To test a successful transaction, use valid name and address information.
- To test a declined transaction, use invalid information, such as an invalid address for Delivery Address Verification or information with missing fields.
- When testing the Simple Order API, use the following test URL:
<https://ics2wstesta.ic3.com/commerce/1.x/transactionProcessor>

If your system is configured correctly, you receive a reply with the expected reply fields and reason codes. See "[Reply Fields](#)," page 33, and "[Reason Codes](#)," page 39.

If your tests are successful, contact your Cybersource representative to activate your account so that you can send transactions to the Cybersource production server. To process customer transactions, you must change the status of your account from test to live production.

After you start processing transactions on the production server, you can configure Cybersource reports. For more information, see the *Reporting Developer's Guide* ([PDF](#) | [HTML](#)).

Testing Export Compliance

Use one of the following sets of request values to test your Export Compliance Service. Include first name and last name.

billTo_firstName	Mohammed
billTo_lastName	QASIM

OR

billTo_firstName	Maria
billTo_lastName	RODRIGUEZ

Table 5 provides possible reply values.

Table 5 Possible Reply Field Values for Export Compliance Service

Scenario	Request Field Values	Response
Matching first/last name (case insensitive)	billTo_firstName =Mohammed	exportReply_reasonCode =100
	billTo_lastName =QASIM	exportReply_infoCode =MATCH-DPC
		exportReply_ipCountryConfidence =-1
		deniedPartiesMatch_1_address_1 =Waish,Spin Boldak,null,
		deniedPartiesMatch_1_address_2 =Bypass Road,Chaman,null,
		deniedPartiesMatch_1_address_3 =Karez Qaran,Musa Qal'ah,Helmand Province,null,
		deniedPartiesMatch_1_address_4 =Qalaye Haji Ali Akbar Dalbandin Post Office,,null,
		deniedPartiesMatch_1_address_5 =Room 33, 5th Floor Sarafi Market,Kandahar,,null,
		deniedPartiesMatch_1_address_6 =Safaar Bazaar,Garmsir,,null,
		deniedPartiesMatch_1_list =Office of Foreign Assets Control
		deniedPartiesMatch_1_name_1 =Mohammed QASIM
		deniedPartiesMatch_1_name_2 =aka, QASIM, Muhammad
		deniedPartiesMatch_1_program =SDGT
		reasonCode =100

Table 5 Possible Reply Field Values for Export Compliance Service (Continued)

Scenario	Request Field Values	Response
Matching first/last name (case insensitive)	billTo_firstName =Maria billTo_lastName =RODRIGUEZ	exportReply_reasonCode =100 exportReply_infoCode =MATCH-DPC exportReply_ipCountryConfidence = -1 deniedPartiesMatch_1_list =Office of Foreign Assets Control deniedPartiesMatch_1_name_1 =Maria de Jesus ESPINOZA RODRIGUEZ deniedPartiesMatch_1_program =SDNTK reasonCode =100
Non-matching first/last name	Use any value.	exportReply_reasonCode =100 exportReply_ipCountryConfidence =-1 reasonCode =100

API Fields


Important

- If you use Delivery Address Verification for non-U.S. requests, use version 1.31 or later of the Simple Order API.
- Download the API from the following URL:
<https://ics2ws.ic3.com/commerce/1.x/transactionProcessor>

Formatting Restrictions

Unless otherwise noted, all field names are case sensitive and all fields accept special characters such as @, #, and %.


Important

- The values of the item_#_ fields must not contain carets (^) or colons (:) because these characters are reserved for use by Cybersource services.
- The values of all request fields must not contain new lines or carriage returns. However, they can contain embedded spaces and any other printable characters. All leading and trailing spaces will be removed.

Data Type Definitions

For more information about these data types, see the World Wide Web Consortium (W3C) XML Schema Part 2: Datatypes specification:

<http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

Data Type	Description
Integer	Whole number {..., -3, -2, -1, 0, 1, 2, 3, ...}
String	Sequence of letters, numbers, spaces, and special characters, such as @ or #.

Numbered Elements

Request Fields

See *Getting Started with Cybersource Advanced for the Simple Order API* ([PDF](#) | [HTML](#)) for a description of how name-value pair names relate to their corresponding XML element names.

Table 6 Request Fields

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
billTo_city	City of the billing address. If shipTo_city is not provided, billTo_city is used in its place for davService .	davService (R) exportService (R)	String (50)
billTo_company	Company name of person buying the product. Important This field or billTo_firstName and billTo_lastName must be present. Otherwise, your request will fail.	exportService (see description)	String (60)
billTo_country	Country of the billing address. Use the two-character country or region codes (see " Country or Region and Territory Postal System Categories ," page 59). If shipTo_country is not provided, billTo_country is used in its place for davService .	davService (R) exportService (R)	String (2)
billTo_customerID	Customer's account ID, tracking number, reward number, or other unique number that you can assign to the customer.	davService (O) exportService (O)	String (100)
billTo_email	Customer's email address, including the full domain name. The field must be submitted in the form name@host.domain (for example, jdoe@Cybersource.com).	exportService (R)	String (255)
billTo_firstName	Customer's first name. Important If you submit this field, you must also submit billTo_lastName . Alternatively, you can submit billTo_company field instead of billTo_firstName and billTo_lastName . Otherwise, your request will fail.	exportService (see description)	String (60)
billTo_hostname	DNS resolved host name from billTo_ipAddress .	exportService (O)	String (40)

Table 6 Request Fields (Continued)

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
billTo_ipAddress	IP address of the customer (for example, 10.1.27.63).	exportService (O)	String (15)
billTo_lastName	Customer's last name. Important If you submit this field, you must also submit billTo_firstName . Alternatively, you can submit billTo_company field instead of billTo_firstName and billTo_lastName . Otherwise, your request will fail.	exportService (see description)	String (60)
billTo_postalCode	Postal code of the billing address. Make sure that you send only valid and well-formed data. Required only if the billTo_country field is US or CA: <ul style="list-style-type: none"> ■ US: numeric characters in either of these formats: <ul style="list-style-type: none"> • five characters: NNNNN • nine characters: NNNNN-NNNN ■ CA: six alphanumeric characters in this format: ANA NAN 	davService (required for U.S. and Canada)	String (10)
billTo_state	State or province of the billing address. Use the two-character codes located in the Support Center . If the shipping address information is not provided, billTo_state is used in place of shipTo_state for davService . Required if the value of billTo_country is CA or US.	davService (O) exportService (O)	String (2)
billTo_street1	First line of the billing address.	davService (R) exportService (R)	String (60)
billTo_street2	Second line of the billing address.	davService (O) exportService (O)	String (60)
billTo_street3 to billTo_Street4	Third and fourth line of the billing address.	davService (O)	String (60)

Table 6 Request Fields (Continued)

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
businessRules_ignoresDAVResult	Use when requesting davService with other services. Allows you to continue processing the request even if davService cannot verify the address. This field can contain one of these values: <ul style="list-style-type: none"> ■ true: Ignore the results of address verification and continue to process the request. ■ false: (default) If davService cannot verify the address, stop processing the request. 	davService (O)	String (5)
businessRules_ignoresExportResult	Use when requesting exportService with other services or if the Denied Parties Check (DPC) is enabled for your Cybersource merchant ID. Allows you to continue processing the request even if the order does not pass Export Compliance. This field can contain one of these values: <ul style="list-style-type: none"> ■ true: Ignore the results of Export Compliance and continue to process the request. The reply will include information about any DPC match. ■ false: (default) If the order does not pass Export Compliance, stop processing the request. 	exportReply (O)	String (5)
comments	Brief description of the order or any comment that you wish to add to the order.	davService (O) exportReply (O)	String (255)
davService_run	Indicates whether to include davService in your request. The field can contain one of these values: <ul style="list-style-type: none"> ■ true: Include the service in your request. ■ false: (default) Do not include the service in your request. 	davService (O)	String (5)

Table 6 Request Fields (Continued)

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
exportService_ addressOperator	<p>Parts of the customer's information that must match with an entry in the DPL before a match occurs. This field can contain one of these values:</p> <ul style="list-style-type: none"> ■ AND: (default) The customer's name or company <i>and</i> the customer's address must appear in the database. ■ OR: The customer's name must appear in the database. ■ IGNORE: You want the service to detect a match only of the customer's name or company but not of the address. 	exportService (O)	String (3)
exportService_ addressWeight	<p>Degree of correlation between a customer's address and an entry in the DPL before a match occurs. This field can contain one of these values:</p> <ul style="list-style-type: none"> ■ exact: The address must be identical to the entry in the DPL. ■ high: (default) The address cannot differ significantly from the entry in the DPL. ■ medium: The address can differ slightly more from the entry in the DPL. ■ low: The address can differ significantly from the entry in the DPL. 	exportService (O)	String (6)
exportService_ companyWeight	<p>Degree of correlation between a company name and an entry in the DPL before a match occurs. This field can contain one of these values:</p> <ul style="list-style-type: none"> ■ exact: The company name must be identical to the entry in the DPL. ■ high: (default) The company name cannot differ significantly from the entry in the DPL. ■ medium: The company name can differ slightly more from the entry in the DPL. ■ low: The company name can differ significantly from the entry in the DPL. 	exportService (O)	String (6)

Table 6 Request Fields (Continued)

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
exportService_nameWeight	<p>Degree of correlation between a customer's name and an entry in the DPL before a match occurs. This field can contain one of these values:</p> <ul style="list-style-type: none"> ■ exact: The name must be identical to the entry in the DPL. ■ high: (default) The name cannot differ significantly from the entry in the DPL. ■ medium: The name can differ slightly more from the entry in the DPL. ■ low: The name can differ significantly the entry in the DPL. 	exportService (O)	String (6)
exportService_run	<p>Indicates whether to include exportService in your request. The field can contain one of these values:</p> <ul style="list-style-type: none"> ■ true: Include the service in your request. ■ false: (default) Do not include the service in your request. 	exportService (O)	String (5)
exportService_sanctionsLists	<p>Use this field to specify which list(s) you want checked with the request. The reply will include the list name as well as the response data.</p> <p>To check against multiple lists, enter multiple list codes separated by a caret (^).</p> <p>For more information, see "Restricted and Denied Parties List," page 68.</p>	exportService (O)	String (255)
item_#_export	<p>List of ISO country or region codes for countries to which the product can be exported. For more information, see "Country or Region and Territory Postal System Categories," page 59.</p> <p>Separate the codes by a single space, for example: <code>item_0_export=AF AL DZ</code></p> <p>If the ISO country codes are not specified or if this field is left blank, the U.S. government's country code list is used.</p> <p>Note The default list of countries restricted by the U.S. always applies. Any country not specifically added to the item_#_export field is considered restricted.</p> <p>See "Numbered Elements," page 26.</p>	exportService (O)	String (no length limit)

Table 6 Request Fields (Continued)

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
item_#_noExport	<p>List of ISO country or region codes for countries to which the product cannot be exported. For more information, see "Country or Region and Territory Postal System Categories," page 59.</p> <p>Separate the codes by a single space, for example, <code>item_0_noExport=AF AL DZ</code></p> <p>Note If the <code>item_#_export</code> field is also present, the content of <code>item_#_noExport</code> overrides the content of <code>item_#_export</code>.</p> <p>See "Numbered Elements," page 26.</p>	exportService (O)	String (no length limit)
item_#_productCode	<p>Type of product that the item contains, which is also used to determine the category within which the product falls (electronic, handling, physical, service, or shipping).</p> <p>Multiple productCode values can apply to the same item (for example, shipping and handling). The default value is <code>default</code>. For more information, see "Product Codes," page 58.</p> <p>See "Numbered Elements," page 26.</p>	davService (O) exportService (O)	String (30)
item_#_productName	<p>Name of the product.</p> <p>See "Numbered Elements," page 26.</p>	davService (O) exportService (O)	String (30)
item_#_productSKU	<p>Product's identifier code.</p> <p>See "Numbered Elements," page 26.</p>	davService (O) exportService (O)	String (30)
item_#_quantity	<p>Quantity of the product being purchased.</p> <p>See "Numbered Elements," page 26.</p>	davService (O) exportService (O)	Integer (10)
item_#_unitPrice	<p>Per-item price of the product. This value cannot be negative. You can include a decimal point (.) in this field, but you cannot include any other special characters. The amount is truncated at the request level to the correct number of decimal places.</p> <p>See "Numbered Elements," page 26.</p>	davService (R) exportService (R)	String (15)
merchantID	<p>Your Cybersource merchant ID. Use the same merchant ID for evaluation, testing, and production.</p>	davService (R) exportService (R)	String (30)

Table 6 Request Fields (Continued)

Field	Description	Used By: Required (R) or Optional (O)	Data Type & Length
merchantReferenceCode	Merchant-generated order reference or tracking number.	davService (R) exportService (R)	String (50)
shipTo_city	City of the shipping address.	davService (R)	String (50)
shipTo_country	Country of the shipping address. Use the two-character country or region codes (see "Country or Region and Territory Postal System Categories," page 59). For exportService, billTo_country is used if shipTo_country is not present.	davService (R) exportService (O)	String (2)
shipTo_firstName	First name of the recipient.	exportService (O)	String (60)
shipTo_lastName	Last name of the recipient.	exportService (O)	String (60)
shipTo_postalCode	Postal code of the shipping address. Required if the value of shipTo_country is CA or US.	davService (O)	String (10)
shipTo_state	State or province of the shipping address. Use the State, Province, and Territory Codes for the United States and Canada . The default value for shipTo_state is the value of billTo_state . Required if the value of shipTo_country is CA or US.	davService (O)	String (2)
shipTo_street1	First line of the shipping address.	davService (R)	String (60)
shipTo_street2 to shipTo_street4	Second to fourth line of the shipping address.	davService (O)	String (60)

Reply Fields

Table 7 Reply Fields

Field	Description	Returned By	Data Type & Length
davReply_addressType	<p>Contains the record type of the postal code with which the address was matched.</p> <p>U.S. Addresses</p> <p>Depending on the quantity and quality of the address information provided, this field contains one or two characters:</p> <p>One character: sufficient correct information was provided to result in accurate matching.</p> <p>Two characters: standardization would provide a better address if more or better input address information were available. The second character is D (default).</p> <p>Blank fields are unassigned. When an address cannot be standardized, how the input data was parsed determines the address type. In this case, standardization may indicate a street, rural route, highway contract, general delivery, or PO box. For possible values, see Appendix H, "Address Type," on page 73.</p> <p>All Other Countries</p> <p>This field contains one of these values:</p> <ul style="list-style-type: none"> ■ P: Post. ■ S: Street. ■ x: Unknown. 	davReply	String (255)
davReply_barCode	Delivery point bar code determined from the input address.	davReply	String (255)
davReply_barCodeCheckDigit	Verification digit for the 11-digit delivery point bar code.	davReply	Integer (1)
davReply_caErrorInfo	Four-character error code returned for Canadian addresses. For possible values, see "Error Codes: International Addresses," page 49.	davReply	String (255)
davReply_calInfo	Four-to-ten character status code returned for Canadian addresses. For possible values, see "Status Codes: International Addresses," page 45.	davReply	String (255)
davReply_careOf	<i>Care of</i> data dropped from the standard address.	davReply	String (255)

Table 7 Reply Fields (Continued)

Field	Description	Returned By	Data Type & Length
davReply_countryErrorInfo	Four-character error code returned for international addresses. For possible values, see "Error Codes: International Addresses," page 49.	davReply	String (255)
davReply_intlErrorInfo	Four-character error code returned for international addresses. For possible values, see "Error Codes: International Addresses," page 49.	davReply	String (255)
davReply_intlInfo	Four-to-ten character status code returned for international addresses. For possible values, see "Status Codes: International Addresses," page 45.	davReply	String (255)
davReply_matchScore	Indicates the probable correctness of the address match. Returned for U.S. and Canadian addresses. Returns a value from 0-9, where 0 is most likely to be correct and 9 is least likely to be correct, or -1 if there is no address match.	davReply	Integer (1)
davReply_reasonCode	A numeric value corresponding to the result of the Delivery Address Verification request. For a list of possible values, see "Reason Codes," page 39.	davReply	Integer (5)
davReply_standardizedAddress1	First line of the standardized address, including apartment information.	davReply	String (255)
davReply_standardizedAddress2 to davReply_standardizedAddress4	Second to fourth line of the standardized address.	davReply	String (255)
davReply_standardizedAddressNoApt	First line of the standardized address, without apartment information. Returned for U.S. and Canadian addresses.	davReply	String (255)
davReply_standardizedCity	Standardized city name.	davReply	String (255)
davReply_standardizedCountry	Standardized country name.	davReply	String (255)
davReply_standardizedCounty	Standardized county name.	davReply	String (255)
davReply_standardizedCSP	Standardized city, state or province, and ZIP+4 code or postal code line.	davReply	String (255)
davReply_standardizedISOCountry	Standardized two-character ISO country code.	davReply	String (255)
davReply_standardizedPostalCode	Standardized U.S. ZIP+4 code or postal code.	davReply	String (255)

Table 7 Reply Fields (Continued)

Field	Description	Returned By	Data Type & Length
davReply_standardizedState	U.S. Postal Service standardized state or province abbreviation.	davReply	String (255)
davReply_usErrorInfo	Four-character error code returned for U.S. addresses; for possible values, see "Error Codes: U.S. Addresses," page 48.	davReply	String (255)
davReply_usInfo	Four-to-ten character status code returned for U.S. addresses; for possible values, see "Status Codes: U.S. Addresses," page 41.	davReply	String (255)
decision	Summarizes the result of the overall request. The field can contain one of these values: <ul style="list-style-type: none"> ■ ACCEPT ■ ERROR ■ REJECT 	davReply exportReply	String (255)
deniedPartiesMatch_N_address_0 through deniedPartiesMatch_N_address_N	Address found on the list specified in deniedPartiesMatch_N_list for the entity (name and address) in the request.	exportReply	String (255)
deniedPartiesMatch_N_list	List on which the first DPC correlation appears. For a list of codes, see "Denied Parties List Check Codes," page 56.	exportReply	String (255)
deniedPartiesMatch_N_name_0 through deniedPartiesMatch_N_name_N	Name found in the list specified in deniedPartiesMatch_N_list for the entity (name and address) in the request.	exportReply	String (255)
deniedPartiesMatch_N_program_N	Sub-lists matched by the order data. List members are separated by carets (^).	exportReply	String (255)

Table 7 Reply Fields (Continued)

Field	Description	Returned By	Data Type & Length
exportReply_infoCode	<p>Returned when the Denied Parties List check (first two codes) or the export service (all others) would have declined the transaction. This field can contain one or more of these values:</p> <ul style="list-style-type: none"> ■ MATCH-DPC: Denied Parties List match. ■ UNV-DPC: Denied Parties List unavailable. ■ MATCH-BCO: Billing country restricted. ■ MATCH-EMCO: Email country restricted. ■ MATCH-HCO: Host name country restricted. ■ MATCH-IPCO: IP country restricted. ■ MATCH-SCO: Shipping country restricted. <p>Multiple information codes are separated by a caret (^). For more information, see "Excluding Export Compliance Results," page 18.</p>	exportReply	String (255)
exportReply_ipCountryConfidence	Likelihood that the country associated with the customer's IP address was identified correctly. Returns a value from 1-100; 100 indicates the highest likelihood. If the country cannot be determined, the value is -1.	exportReply	Integer (3)
exportReply_reasonCode	Numeric value corresponding to the result of the Export Compliance service request. For possible values, see "Reason Codes," page 39.	exportReply	Integer (5)
invalidField_0 through invalidField_N	Fields in the request that contained invalid data.	davReply exportReply	String (255)
merchantReferenceCode	Merchant-generated order tracking number.	davReply exportReply	String (255)
missingField_0 through missingField_N	Required fields that are missing from the request.	davReply exportReply	String (255)
reasonCode	Numeric value corresponding to the result of the overall request. For possible values, see "Reason Codes," page 39.	davReply exportReply	Integer (5)
requestID	Identifier for the request.	davReply exportReply	String (255)

Table 7 Reply Fields (Continued)

Field	Description	Returned By	Data Type & Length
requestToken	<p>Request identifier generated by Cybersource.</p> <p>Request token data created by CyberSource for each reply. The field is an encoded string that contains no confidential information such as an account or card verification number. The string can contain a maximum of 256 characters.</p>	<p>davReply</p> <p>exportReply</p>	String (256)

Reason Codes

The following table describes the reason codes returned by the Simple Order API for Verification Services. For a description of replies, decisions, and reason codes, see the information about handling replies in *Getting Started with Cybersource Advanced for the Simple Order API* ([PDF](#) | [HTML](#)).



Important

Because Cybersource can add reply fields and reason codes at any time, your error handler must:

- Parse the reply data according to the names of the fields instead of their order in the reply. For more information about parsing reply fields, see the documentation for your client.
- Use the decision fields to obtain the result if it receives a reason code that it does not recognize.

Table 8 Reason Codes

Reason Code	Description	Returned By
100	Successful transaction.	davReply exportReply
101	The request is missing one or more required fields. Possible action: See the reply fields missingField_0 through missingField_N for the missing fields. Resend the request with the complete information.	davReply exportReply
102	One or more fields in the request contains invalid data. Possible action: See the reply fields invalidField_0 through invalidField_N for the invalid fields. Resend the request with the correct information.	davReply exportReply
150	Error: General system failure. Possible action: Wait a few minutes and resend the request.	davReply exportReply
151	Error: The request was received but the server timed out. This error does not include timeouts between the client and the server. Possible action: Wait a few minutes and resend the request.	davReply exportReply
152	Error: The request was received but the service timed out. Possible action: Wait a few minutes and resend the request.	davReply exportReply

Table 8 Reason Codes (Continued)

Reason Code	Description	Returned By
234	A problem exists with your Cybersource merchant configuration. Possible action: Do not resend the request. Contact Customer Support to correct the configuration problem.	davReply exportReply
450	The apartment number missing or not found. Possible action: Ask the customer to verify the address information and resend the request.	davReply
451	The request contains insufficient the address information. Possible action: Ask the customer to verify the address information and resend the request.	davReply
452	The house number or post office box identifier cannot be found on the specified street. Possible action: Ask the customer to verify the address information and resend the request.	davReply
453	Multiple address matches were found. This code is returned only for U.S. addresses. Possible action: Ask the customer to verify the address information and resend the request.	davReply
454	The post office box identifier cannot be found or is out of range. Possible action: Ask the customer to verify the address information and resend the request.	davReply
455	The route service identifier cannot be found or is out of range. Possible action: Ask the customer to verify the address information and resend the request.	davReply
456	The street name cannot be found in the specified postal code. Possible action: Ask the customer to verify the address information and resend the request.	davReply
457	The postal code cannot be found. Possible action: Ask the customer to verify the address information and resend the request.	davReply
458	The address cannot be verified or corrected. Possible action: Ask the customer to verify the address information and resend the request.	davReply
459	Multiple address matches were found; returned for only non-U.S. addresses. Possible action: Ask the customer to verify the address information and resend the request.	davReply
460	An address match cannot be found; No reason can be given. Possible action: Ask the customer to verify the address information and resend the request.	davReply

Table 8 Reason Codes (Continued)

Reason Code	Description	Returned By
461	The character set is not supported by the address verification service. Possible action: Verify the character set that you are using to process transactions.	davReply
700	The customer is on a list issued by a government agency containing entities with whom trade is restricted. Possible action: Reject the customer's order.	exportReply
701	One or both of these events occurred: <ul style="list-style-type: none"> ■ A government agency maintains an embargo against the country indicated in the billing or shipping address. ■ You supplied an export list for one or more of the offers in the order, but the shipping country submitted by the customer is not in that list. Possible action: Reject the customer's order.	exportReply
702	A government agency maintains an embargo against the country associated with the email address. Possible action: Reject the customer's order.	exportReply
703	A government agency maintains an embargo against the country associated with the IP address. Possible action: Reject the customer's order.	exportReply

Status and Error Codes

This appendix describes the status and error codes that are returned in API reply fields for U.S. and international addresses. *Status codes* contain information about corrections or standardizations that are applied to an address. *Error codes* contain information that explains why an address cannot be verified. Status and error codes are returned in the following reply fields:

Table 11 Status and Error Code API Reply Fields

Status Codes	Error Codes
davReply_usInfo	davReply_usErrorInfo
davReply_caInfo	davReply_caErrorInfo
davReply_intlInfo	davReply_intlErrorInfo

Status Codes: U.S. Addresses

Table 12 Status Codes Returned for U.S. Addresses

Ordinal Digit	Value	Description
1st	A	Address line is truncated to make it fit into the field.
	B	Both the address line and the city name are truncated.
	C	City name is truncated to make it fit into the field.
	S	Nothing is truncated.

Table 12 Status Codes Returned for U.S. Addresses (Continued)

Ordinal Digit	Value	Description
	0	No significant difference between input and corrected data for city, state, ZIP, and ZIP+4.
	1	Corrected the ZIP.
	2	Corrected the city.
	3	Corrected the city and ZIP.
	4	Corrected the state.
	5	Corrected the state and ZIP.
	6	Corrected the city and state.
2nd	7	Corrected the city, state, and ZIP.
	8	Corrected the ZIP+4.
	9	Corrected the ZIP and ZIP+4.
	A	Corrected the city and ZIP+4.
	B	Corrected the city, ZIP, and ZIP+4.
	C	Corrected the state and ZIP+4.
	D	Corrected the state, ZIP, and ZIP+4.
	E	Corrected the city, state, and ZIP+4.
	F	Corrected the city, state, ZIP, and ZIP+4.

Table 12 Status Codes Returned for U.S. Addresses (Continued)

Ordinal Digit	Value	Description
3rd	0	No significant difference between input and corrected data for primary street name, directional prefix (predirectional), directional suffix (postdirectional), and street-type suffix.
	1	Corrected the street-type suffix.
	2	Corrected the predirectional.
	3	Corrected the predirectional and street-type suffix.
	4	Corrected the postdirectional.
	5	Corrected the street-type suffix and postdirectional.
	6	Corrected the predirectional and postdirectional.
	7	Corrected the predirectional, street-type suffix, and postdirectional.
	8	Corrected the primary street name.
	9	Corrected the primary street name and street-type suffix.
	A	Corrected the predirectional and primary street name.
	B	Corrected the predirectional, primary street name, and street-type suffix.
	C	Corrected the primary street name and postdirectional.
	D	Corrected the primary street name, street-type suffix, and postdirectional.
	E	Corrected the predirectional, primary street name, and postdirectional.
	F	Corrected the predirectional, primary street name, postdirectional, and street-type suffix.

Table 12 Status Codes Returned for U.S. Addresses (Continued)

Ordinal Digit	Value	Description
	0	No significant difference between input and corrected data for county number, CART (carrier-route number), DPBC (delivery point barcode), and unit designator.
	1	Corrected the unit designator.
	2	Corrected the DPBC.
	3	Corrected the DPBC and unit designator.
	4	Corrected the CART.
	5	Corrected the CART and unit designator.
	6	Corrected the CART and DPBC.
4th	7	Corrected the CART, DPBC, and unit designator.
	8	Corrected the county number.
	9	Corrected the county number and unit designator.
	A	Corrected the county number and DPBC.
	B	Corrected the county number, DPBC, and unit designator.
	C	Corrected the county number and CART.
	D	Corrected the county number, CART, and unit designator.
	E	Corrected the county number, CART, DPBC.
	F	Corrected the county number, CART, DPBC, and unit designator.
5th		Reserved for future use.
6th		Reserved for future use.

Status Codes: International Addresses

Table 13 Status Codes Returned for International Addresses

Ordinal Digit	Value	Description
1st	S	Status
	0	No significant difference between input and corrected data for country, postal code, region, and locality.
	1	Corrected the country.
	2	Corrected the postal code.
	3	Corrected the country and postal code.
	4	Corrected the region.
	5	Corrected the country and region.
2nd	6	Corrected the postal code and region.
	7	Corrected the country, postal code, and region.
	8	Corrected the locality.
	9	Corrected the country and locality.
	A	Corrected the postal code and locality.
	B	Corrected the country, postal code, and locality.
	C	Corrected the region and locality.
	D	Corrected the country, region, and locality.
	E	Corrected the postal code, region, and locality.
	F	Corrected the country, postal code, region, and locality.

Table 13 Status Codes Returned for International Addresses (Continued)

Ordinal Digit	Value	Description
3rd	0	No significant difference between input and corrected data for directional prefix (predirectional), directional suffix (postdirectional), primary street type, primary street name, and primary range.
	1	Corrected the predirectional and postdirectional.
	2	Corrected the street type.
	3	Corrected the predirectional, postdirectional, and primary street type.
	4	Corrected the primary street name.
	5	Corrected the predirectional, postdirectional, and primary street name.
	6	Corrected the primary street type and primary street name.
	7	Corrected the predirectional, postdirectional, primary street type, and primary street name.
	8	Corrected the primary range.
	9	Corrected the predirectional, postdirectional, and primary range.
	A	Corrected the primary street type and primary range.
	B	Corrected the predirectional, postdirectional, primary street type, and primary range.
	C	Corrected the primary street name and primary range.
	D	Corrected the predirectional, postdirectional, primary street name, and primary range.
	E	Corrected the primary street type, primary street name, and primary range.
	F	Corrected the predirectional, postdirectional, primary street type, primary street name, and primary range.

Table 13 Status Codes Returned for International Addresses (Continued)

Ordinal Digit	Value	Description
4th	0	No significant difference between input and corrected data for unit description, unit number, building name, and firm name.
	1	Corrected the unit description.
	2	Corrected the unit number.
	3	Corrected the unit description and unit number.
	4	Corrected the building name.
	5	Corrected the unit description and building name.
	6	Corrected the unit number and building name.
	7	Corrected the unit description, unit number, and building name.
	8	Corrected the firm.
	9	Corrected the unit description and firm.
	A	Corrected the unit number and firm.
	B	Corrected the unit description, unit number, and firm.
	C	Corrected the building name and firm.
	D	Corrected the unit description, building name, and firm.
	E	Corrected the unit number, building name, and firm.
	F	Corrected the unit description, unit number, building name, and firm.
5th	0	No significant difference between input and corrected data for other components that are not considered basic address components.
	1	Corrected other primary address components.
	2	Corrected other secondary address components.
	3	Corrected other primary and secondary address components.
6th	A	Europe, Middle East, and Africa (EMEA) engine: archived record used for assignment.
	B	Global address engine (New Zealand): base record assignment.
	I	Global address engine (New Zealand): record ignored.
	L	Global address engine (Brazil): Large Volume Receiver (LVR).
	U	Global Address Cleanse (New Zealand): unique address.

Error Codes: U.S. Addresses

Table 14 Error Codes Returned for U.S. Addresses

Code	Description
E101	City, state, or ZIP code is incorrect or missing.
E212	No city and incorrect ZIP code.
E213	Incorrect city, valid state or province, and no ZIP code.
E214	Incorrect city and ZIP code.
E216	Incorrect ZIP code. Cannot determine city.
E302	No primary address line parsed.
E412	Street name not found in directory.
E413	Possible street-name matches too closely to select one.
E420	Primary range is missing.
E421	Primary range is invalid for the street, route, or building.
E422	Predirectional is needed. Input is wrong or missing.
E423	Street-type suffix is needed. Input is wrong or missing.
E425	Street-type suffix, predirectional, or postdirectional is needed. Input is wrong or missing.
E427	Postdirectional is needed. Input is wrong or missing.
E428	Incorrect ZIP code. Cannot match address.
E429	Incorrect city. Cannot match address.
E430	Possible address-line matches too closely to select one.
E431	Urbanization needed. Input is wrong or missing.
E439	Exact match made in EWS (Early Warning System) directory of the USPS.
E500	Other error.
E501	Foreign address.
E502	Input record blank.
E503	ZIP code is not in the area covered by the partial ZIP+4 directory.
E504	Overlapping ranges in the ZIP+4 directory.
E505	Address is not in the USPS directories. Undeliverable address.
E600	Marked by the USPS as unsuitable for mail delivery.
E601	Primary address number not in DPV (Delivery Point Validation) database of the USPS, and ZIP+4 was removed.

Error Codes: International Addresses

Table 15 Error Codes Returned for International Addresses

Code	Description
Input Record Discrepancies	
1020	Address validated in multiple countries.
1030	Country code invalid or absent from the request.
1040	At least one address character not in supported character set.
1060	Country is not supported.
Inconsistent Last Line Information	
2000	Unable to identify the locality, state, or postal code.
2010	Unable to identify the locality. Invalid postal code.
2020	Unable to identify the postal code. Invalid locality that prevents possible address correction.
2030	Invalid locality and postal code that prevents possible address correction.
2040	Invalid postal code that prevents locality selection.
2050	Last line matches too closely to select one. Last line of address, which depends on the country's address format, is incorrect. For example, in the U.S., last lines of an address should contain city, state, and postal code.
Inconsistent Address Information	
3000	Unable to identify the primary address line. Valid locality, region, and postal code.
3010	Unable to match primary name to the directory. Valid locality, region, and postal code.
3020	Possible primary name matches too closely to select one.
3030	Valid primary street name but missing range.
3040	Valid primary street name but invalid range.
3050	Invalid or missing primary street type that prevents a possible address match.
3060	Missing primary street type and directional information that prevents possible address match.
3070	Invalid or missing directional information that prevents possible address match.
3080	Invalid or missing postal code that prevents possible address match.
3090	Invalid locality that prevents possible address match.
3100	Possible address line matches too closely to select one.
3110	Address conflicts with postal code. The same primary street name has a different postal code.
Address with Low Likelihood of Delivery	
4000	Invalid or missing secondary address that prevents a possible secondary address line match. Locality, region, postal code, and primary address are valid.
4010	Possible secondary address matches too closely to select one.

Table 15 Error Codes Returned for International Addresses (Continued)

Code	Description
All Other Types of Information	
5000	Valid address, but address is classified undeliverable by a postal authority.
5010	Address is not in specified country.
5020	Blank input record.
6000	Unclassified error.

Request and Reply Examples

Delivery Address Verification Examples

The service requested is **davService**.

Name-Value Pair Request

```
davService_run=true  
merchantID=example  
merchantReferenceCode=482046C3A7E94F5  
billTo_street1=1295 charleston boulevard  
billTo_city=Mtn view  
billTo_state=ca  
billTo_postalCode=94043  
billTo_country=us
```

Name-Value Pair Reply

The following example shows a reply that uses the name-value pair. Depending on the results, some of the fields may be returned empty. Note the status code of S80000 returned by **davReply_usInfo**.

```
requestID=0183045530000167905080
merchantReferenceCode=482046C3A7E94F5
decision=ACCEPT
reasonCode=100
davReply_reasonCode=100
davReply_addressType=S
davReply_barCode=130795
davReply_barCodeCheckDigit=5
davReply_careOf=
davReply_matchScore=2
davReply_standardizedAddress1=1295 Charleston Rd
davReply_standardizedAddress2=
davReply_standardizedAddressNoApt=1295 Charleston Rd
davReply_standardizedCity=Mountain View
davReply_standardizedCSP=Mountain View CA 94043-1307
davReply_standardizedState=CA
davReply_standardizedPostalCode=94043-1307
davReply_standardizedCounty=Santa Clara
davReply_standardizedCountry=US
davReply_standardizedISOCountry=US
davReply_usInfo=S80000
```

XML Request



Important

The following XML examples contain an API version number. Do not use that version number because it may not be the most current. To find the most current version of the API, see <https://ics2ws.ic3.com/commerce/1.x/transactionProcessor>. For transactions in India, see <https://ics2ws.in.ic3.com/commerce/1.x/transactionProcessor>

```
<requestMessage xmlns="urn:schemas-Cybersource-com:transaction-data-1.23">
  <merchantID>example</merchantID>
  <merchantReferenceCode>482046C3A7E94F5</merchantReferenceCode>
  <billTo>
    <street1>1295 charleston boulevard</street1>
    <city>Mtn view</city>
    <state>ca</state>
    <postalCode>94043</postalCode>
    <country>us</country>
  </billTo>
  <davService run="true"/>
</requestMessage>
```

XML Reply

Depending on the results, some of the elements may be returned empty.

```

<c:replyMessage xmlns:c="urn:schemas-Cybersource-com:transaction-data-1.23">
  <c:requestID>0183045530000167905080</c:requestID>
  <c:merchantReferenceCode>482046C3A7E94F5</c:merchantReferenceCode>
  <c:decision>ACCEPT</c:decision>
  <c:reasonCode>100</c:reasonCode>
  <c:davReply>
    <c:reasonCode>100</c:reasonCode>
    <c:addressType>S</c:addressType>
    <c:apartmentInfo/>
    <c:barCode>130795</c:barCode>
    <c:barCodeCheckDigit>5</c:barCodeCheckDigit>
    <c:careOf/>
    <c:cityInfo>C</c:cityInfo>
    <c:directionalInfo/>
    <c:matchScore>2</c:matchScore>
    <c:standardizedAddress1>1295 Charleston Rd
  </c:standardizedAddress1>
    <c:standardizedAddress2/>
    <c:standardizedAddressNoApt>1295 Charleston Rd
  </c:standardizedAddressNoApt>
    <c:standardizedCity>Mountain View</c:standardizedCity>
    <c:standardizedCounty>Santa Clara</c:standardizedCounty>
    <c:standardizedCSP>Mountain View CA 94043-1307
  </c:standardizedCSP>
    <c:standardizedState>CA</c:standardizedState>
    <c:standardizedPostalCode>94043-1307</c:standardizedPostalCode>
    <c:standardizedCountry>US</c:standardizedCountry>
    <c:standardizedISOCountry>US</c:standardizedISOCountry>
    <c:stateInfo/>
    <c:suffixInfo>S</c:suffixInfo>
    <c:usInfo>S80000</c:usInfo>
    <c:overallInfo/>
  </c:davReply>
</c:replyMessage>

```

Export Compliance Examples

Example of Declined Transactions

Name-Value Pair Request

```
exportService_run=true
merchantID=example
merchantReferenceCode=482046C3A7E94F5
billTo_firstName=Maria
billTo_lastName=Rodriguez
billTo_street1=1234 First St.
billTo_city=Mountain View
billTo_state=CA
billTo_postalCode=94043
billTo_country=US
billTo_phoneNumber=650-965-6000
billTo_email=maria@example.com
billTo_ipAddress=127.0.0.1
item_0_unitPrice=20.00
item_0_noExport=AF AL DZ
```

Name-Value Pair Reply

```
decision=REJECT
deniedPartiesMatch_1_list=Office of Foreign Assets Control
deniedPartiesMatch_1_name_1=Maria de Jesus ESPINOZA RODRIGUEZ
deniedPartiesMatch_1_program_1=SDNTK
exportReply_infoCode=MATCH-DPC
reasonCode=700
requestID=0305782650000167905080
merchantReferenceCode=482046C3A7E94F5
```

XML Request



Important

The following XML examples contain an API version number. Do not use that version number because it may not be the most current. To find the most current version of the API, see <https://ics2ws.ic3.com/commerce/1.x/transactionProcessor>. For transactions in India, see <https://ics2ws.in.ic3.com/commerce/1.x/transactionProcessor>

```
<requestMessage xmlns="urn:schemas-Cybersource-com:transaction-data-1.23">
  <merchantID>example</merchantID>
  <merchantReferenceCode>482046C3A7E94F5</merchantReferenceCode>
  <billTo>
    <firstName>Maria</firstName>
    <lastName>Rodriguez</lastName>
    <street1>1234 First St.</street1>
    <city>Mountain View</city>
    <state>CA</state>
    <postalCode>94043</postalCode>
    <country>US</country>
    <phoneNumber>650-965-6000</phoneNumber>
    <email>maria@example.com</email>
    <ipAddress>127.0.0.1</ipAddress>
  </billTo>
  <item id="0">
    <unitPrice>20.00</unitPrice>
    <noExport>AF AL DZ</noExport>
  </item>
  <exportService run="true">
  </exportService>
</requestMessage>
```

XML Reply

```
<c:replyMessage xmlns:c="urn:schemas-Cybersource-com:transaction-data-1.23">
  <c:requestID>0305782650000167905080</c:requestID>
  <c:merchantReferenceCode>482046C3A7E94F5</c:merchantReferenceCode>
  <c:decision>REJECT</c:decision>
  <c:reasonCode>700</c:reasonCode>
  <c:deniedPartiesMatch>
    <c:list>Office of Foreign Assets Control</c:list>
    <c:name>Maria de Jesus ESPINOZA RODRIGUEZ</c:name>
    <c:program>SDNTK</c:program>
  </c:deniedPartiesMatch>
  <c:exportReply>
    <c:reasonCode>700</c:reasonCode>
    <c:ipCountryConfidence>-1</c:ipCountryConfidence>
    <c:infoCode>MATCH-DPC</c:infoCode>
  </c:exportReply>
</c:replyMessage>
```

Name and Address Word Matching Examples

The following request examples specify that for a match to occur:

- The address must be very near an entry on a DPL (Denied Parties List).

In the name-value pair example, **exportService_addressWeight** is set to `high`. In the XML example, `<addressWeight>` is set to `high`.

- The customer name or company name can differ slightly more.

In the name-value pair example, **exportService_nameWeight** and **exportService_companyWeight** are set to `medium`. In the XML example, `<nameWeight>` and `<companyWeight>` are set to `medium`.

For more information about adjusting how names and addresses are matched with DPLs, see ["Adjusting Name and Address Word Matching," page 20](#).

Name-Value Pair Request

```
exportService_run=true  
merchantID=example  
merchantReferenceCode=482046C3A7E94F5  
billTo_firstName=John  
billTo_lastName=Doe  
billTo_street1=1295 Charleston Rd.  
billTo_city=Mountain View  
billTo_state=CA  
billTo_postalCode=94043  
billTo_country=US  
billTo_phoneNumber=650-965-6000  
billTo_email=jdoe@example.com  
billTo_ipAddress=127.0.0.1  
item_0_unitPrice=20.00  
item_0_noExport=AF AL DZ  
exportService_addressWeight=high  
exportService_companyWeight=medium  
exportService_nameWeight=medium
```

Name-Value Pair Reply

```
requestID=0305782650000167905080  
merchantReferenceCode=482046C3A7E94F5  
decision=ACCEPT  
reasonCode=100  
exportReply_reasonCode=100  
exportReply_ipCountryConfidence=98
```

XML Request



Important

The following XML examples contain an API version number. Do not use that version number because it may not be the most current. To find the most current version of the API, see <https://ics2ws.ic3.com/commerce/1.x/transactionProcessor>. For transactions in India, see <https://ics2ws.in.ic3.com/commerce/1.x/transactionProcessor>

```
<requestMessage xmlns="urn:schemas.-Cybersource-com:transaction-data-1.23">
  <merchantID>example</merchantID>
  <merchantReferenceCode>482046C3A7E94F5</merchantReferenceCode>
  <billTo>
    <firstName>John</firstName>
    <lastName>Doe</lastName>
    <street1>1295 Charleston Rd.</street1>
    <city>Mountain View</city>
    <state>CA</state>
    <postalCode>94043</postalCode>
    <country>US</country>
    <phoneNumber>650-965-6000</phoneNumber>
    <email>jdoe@example.com</email>
    <ipAddress>127.0.0.1</ipAddress>
  </billTo>
  <item id="0">
    <unitPrice>20.00</unitPrice>
    <noExport>AF AL DZ</noExport>
  </item>
  <exportService run="true">
    <addressWeight>high</addressWeight>
    <companyWeight>medium</companyWeight>
    <nameWeight>medium</nameWeight>
  </exportService>
</requestMessage>
```

XML Reply

```
<c:replyMessage xmlns:c="urn:schemas-Cybersource-com:transaction-data-1.23">
  <c:requestID>0305782650000167905080</c:requestID>
  <c:merchantReferenceCode>482046C3A7E94F5</c:merchantReferenceCode>
  <c:decision>ACCEPT</c:decision>
  <c:reasonCode>100</c:reasonCode>
  <c:exportReply>
    <c:reasonCode>100</c:reasonCode>
    <c:ipCountryConfidence>98</c:ipCountryConfidence>
  </c:exportReply>
</c:replyMessage>
```

Name and Address Matching Rule Examples

The following request examples specify that for a match to occur, the DPL must include the customer's name or the company name *and* the address with the following fields:

- `exportService_addressOperator=AND` (name-value pair)
- `<addressOperator>AND</addressOperator>` (XML)

For more information about adjusting the rules for matching names and addresses with DPLs, see ["Defining Name and Address Matching Rules," page 20](#).

Name-Value Pair Request

```
exportService_run=true
merchantID=example
merchantReferenceCode=482046C3A7E94F5
billTo_firstName=John
billTo_lastName=Doe
billTo_street1=1295 Charleston Rd.
billTo_city=Mountain View
billTo_state=CA
billTo_postalCode=94043
billTo_country=US
billTo_phoneNumber=650-965-6000
billTo_email=jdoe@example.com
billTo_ipAddress=127.0.0.1
item_0_unitPrice=20.00
item_0_noExport=AF AL DZ
exportService_addressOperator=AND
```

XML Request



Important

The following XML examples contain an API version number. Do not use that version number because it may not be the most current. To find the most current version of the API, see <https://ics2ws.ic3.com/commerce/1.x/transactionProcessor>. For transactions in India, see <https://ics2ws.in.ic3.com/commerce/1.x/transactionProcessor>.

```

<requestMessage xmlns="urn:schemas-Cybersource-com:transaction-data-1.22">
  <merchantID>example</merchantID>
  <merchantReferenceCode>482046C3A7E94F5</merchantReferenceCode>
  <billTo>
    <firstName>John</firstName>
    <lastName>Doe</lastName>
    <street1>1295 Charleston Rd.</street1>
    <city>Mountain View</city>
    <state>CA</state>
    <postalCode>94043</postalCode>
    <country>US</country>
    <phoneNumber>650-965-6000</phoneNumber>
    <email>jdoe@example.com</email>
    <ipAddress>127.0.0.1</ipAddress>
  </billTo>
  <item id="0">
    <unitPrice>20.00</unitPrice>
    <noExport>AF AL DZ</noExport>
  </item>
  <exportService run="true">
    <addressOperator>AND</addressOperator>
  </exportService>
</requestMessage>

```

Export Compliance Standard Codes

Export Compliance returns the following codes.

Denied Parties List Check Codes

The following table contains result codes that are returned for Denied Parties List (DPL) checks. Each code represents one of the denied parties lists that are checked by Export Compliance. These codes are returned in the **deniedPartiesMatch_#_list** reply field. When these codes are returned, Export Compliance has detected a match between order data and an entry in the Denied Parties List represented by the code.

Table 16 Denied Parties List Check Codes

Code	Description
GOV-US-DBR	Debarred Parties List
GOV-US-DPL	Denied Party List, Bureau of Export Administration
GOV-US-ENT	Entity List, Bureau of Export Administration
GOV-US-SDN-BAKN	Balkans List - Specially Designated Nationals List
GOV-US-SDN-BPI-PA	Blocked Pending Investigation - Patriot Act, Specially Designated Nationals List
GOV-US-SDN-CU	Cuba List - Specially Designated Nationals List
GOV-US-SDN-FTO	Foreign Terrorist Organization, Specially Designated Global Terrorist - Specially Designated Nationals List
GOV-US-SDN-IQ	Iraq List - Specially Designated Nationals List
GOV-US-SDN-IR	Iran List - Specially Designated Nationals List
GOV-US-SDN-KP	North Korea List - Specially Designated Nationals List
GOV-US-SDN-LY	Libya List - Specially Designated Nationals List
GOV-US-SDN-SD	Sudan List - Specially Designated Nationals List
GOV-US-SDN-SDFT	Specially Designated Terrorist, Foreign Terrorist Organization, Terrorism List Government Sanctions - Specially Designated Nationals List
GOV-US-SDN-SDGT	Specially Designated Global Terrorist - Specially Designated Nationals List

Table 16 Denied Parties List Check Codes (Continued)

Code	Description
GOV-US-SDN-SDNT	Specially Designated Narcotic Trafficker - Specially Designated Nationals List
GOV-US-SDN-SDNTK	Specially Designated Narcotic Trafficker (Kingpin Act) - Specially Designated Nationals List
GOV-US-SDN-SDT	Specially Designated Terrorist - Specially Designated Nationals List
GOV-US-SDN-SDTG	Specially Designated Terrorist, Terrorism List Government Sanctions Regulations - Specially Designated Nationals List
GOV-US-SDN-TABN	Taliban List - Specially Designated Nationals List
GOV-US-SDN-UNITA	National Union for the Total Independence of Angola & The Armed Forces for the Liberation of Angola - Specially Designated Nationals List
GOV-US-SDN-YU	Federal Republic of Yugoslavia (Milosevic) - Specially Designated Nationals List
GOV-US-SPS-EMB	Embargo List - U.S. Dept. of Commerce, Bureau of Export Administration and Office of Foreign Assets

Product Codes

The following table lists the values that you can use with the `item_#_product_code` request field.

Table 17 Product Codes

Code	Description
<code>adult_content</code>	Adult content.
<code>coupon</code>	Coupon applied to the entire order.
<code>default</code>	Default value for the product code. Cybersource uses <code>default</code> when a request provides no value for the product code.
<code>electronic_good</code>	Electronic product other than software.
<code>electronic_software</code>	Software distributed electronically rather than on tapes, disks, or other media.
<code>gift_certificate</code>	Gift certificate not issued with Cybersource Stored Value Services.
<code>handling_only</code>	Separate charge that is generally a fee imposed by the seller on the customer. The fee pays for the seller's administrative selling costs.
<code>service</code>	Service that you perform for the customer.
<code>shipping_and_handling</code>	Shipping is a separate charge for shipping the product to the purchaser. Handling is generally a fee imposed by the seller to pay for administrative selling costs.
<code>shipping_only</code>	Charge for transporting tangible personal property from the seller to the purchaser. Documentation must be maintained that clearly establishes where title to the tangible personal property passed from the seller to the purchaser.
<code>stored_value</code>	Stored Value certificate.
<code>subscription</code>	Subscription to a web site or other content.

Country or Region and Territory Postal System Categories

This appendix groups countries, regions, and territories according to the similarity of their postal systems. Delivery Address Verification uses the databases maintained by these postal systems to verify order address information.



Important

This note applies to categories II, III, and IV. If Delivery Address Verification cannot verify an address completely, or if the address cannot be matched with a postal database entry, you do not receive a successful reply. If the address is listed in a postal database, the service validates the accuracy of the address provided by the customer. When evaluating the reply of the service, make sure that you consider the error and status codes that also may be present in the reply. See "[Status and Error Codes](#)," page 41.

Category I-A

These countries or regions have rigorous testing and a postal certification process that results in the largest amount and greatest accuracy of postal data.

Table 18 Category I-A Country or Region and Territory Postal Systems

Country or Region	Code
Australia	AU
Canada	CA
United States	US
Includes:	
<ul style="list-style-type: none"> • American Samoa [AS] • Federated States of Micronesia [FM] • Guam [GU] • Marshall Islands [MH] • Northern Mariana Islands [MP] • Palau [PW] • Puerto Rico [PR] • Virgin Islands [VI] 	

Category I-B

These countries or regions provide complete address data, including all street names and all valid address ranges for the buildings on the streets. Although the postal systems of these countries lack the rigor of the Category I-A postal systems, these countries generally provide reasonably accurate and almost complete postal information.

Table 19 Category I-B Country or Region and Territory Postal Systems

Country or Region	Code
Netherlands	NL
United Kingdom	GB
Includes:	
<ul style="list-style-type: none"> • Ireland [IE] 	

Category II

These countries or regions have fairly reliable postal systems and provide street names, city names, and postal codes for large and small cities. However, they provide incomplete ranges for the addresses of buildings. Therefore, you can often trust the validation results for the street name, city name, and postal code, but you cannot trust the validation of building addresses.

Table 20 Category II Country or Region and Territory Postal Systems

Country or Region	Code
Denmark	DK
Includes:	
<ul style="list-style-type: none"> • Faroe Islands [FO] 	
France	FR
Includes:	
<ul style="list-style-type: none"> • French Guiana [GF] • Guadeloupe [GP] • Martinique [MQ] • Reunion [RE] • Mayotte [YT] • Monaco [MC] • Saint Pierre and Miquelon [PM] • French Polynesia [PF] • New Caledonia [NC] • Wallis and Futuna [WF] 	
Germany	DE

Table 20 Category II Country or Region and Territory Postal Systems (Continued)

Country or Region	Code
Switzerland	CH
Includes:	
<ul style="list-style-type: none"> • Liechtenstein [LI] 	

Category III

The postal systems in these countries provide street names, city names, and postal codes for large cities only and incomplete or no information for smaller cities. These postal systems may also provide an extremely limited set of building address ranges. Therefore, you can trust the validation results for city name, street name, and postal code for larger cities. For smaller cities, you can trust validation results for city name and postal code.

Table 21 Category III Country or Region and Territory Postal Systems

Country or Region	Code
Austria	AT
Belgium	BE
Finland	FI
Italy	IT
Includes:	
<ul style="list-style-type: none"> • Vatican City [VA] • San Marino [SM] 	
Luxembourg	LU
New Zealand	NZ
Norway	NO
Poland	PL
Portugal	PT
South Africa	ZA
Spain	ES
Sweden	SE

Category IV

In these countries or regions, the postal systems are highly variable. Most countries or regions provide a list of cities and postal codes. However, all cities and postal codes might not be present in the country's or region's postal database.

Table 22 Category IV Country or Region and Territory Postal Systems

Country or Region	Code
Afghanistan	AF
Albania	AL
Algeria	DZ
Andorra	AD
Angola	AO
Anguilla (UK)	AI
Antigua and Barbuda	AG
Argentina	AR
Armenia	AM
Aruba	AW
Azerbaijan	AZ
Bahamas	BS
Bahrain	BH
Bangladesh	BD
Barbados	BB
Belarus	BY
Belize	BZ
Benin	BJ
Bermuda (UK)	BM
Bhutan	BT
Bolivia	BO
Bosnia and Herzegovina	BA
Botswana	BW
Brazil	BR
British Virgin Islands (UK)	VG
Brunei	BN
Bulgaria	BG
Burkina Faso	BF
Burundi	BI
Cambodia	KH

Table 22 Category IV Country or Region and Territory Postal Systems

Country or Region	Code
Cameroon	CM
Cape Verde	CV
Cayman Islands (UK)	KY
Central African Republic	CF
Chad	TD
Chile	CL
China	CN
Christmas Island (AU)	CX
Cocos (Keeling) Islands (AU)	CC
Columbia	CO
Comoros	KM
Congo, Democratic Republic of the	CD
Congo	CG
Cook Islands (NZ)	CK
Costa Rica	CR
Côte d'Ivoire	CI
Croatia	HR
Cuba	CU
Cyprus	CY
Czech Republic	CZ
Djibouti	DJ
Dominica	DM
Dominican Republic	DO
Ecuador	EC
Egypt	EG
El Salvador	SV
Equatorial Guinea	GQ
Eritrea	ER
Estonia	EE
Ethiopia	ET
Falkland Islands (UK)	FK
Fiji	FJ
Gabon	GA
Gambia	GM
Georgia	GE

Table 22 Category IV Country or Region and Territory Postal Systems

Country or Region	Code
Ghana	GH
Gibraltar (UK)	GI
Greece	GR
Greenland (DK)	GL
Grenada	GD
Guatemala	GT
Guinea	GN
Guinea-Bissau	GW
Guyana	GY
Haiti	HT
Honduras	HN
Hong Kong	HK
Hungary	HU
Iceland	IS
India	IN
Indonesia	ID
Iran	IR
Iraq	IQ
Israel	IL
Jamaica	JM
Japan	JP
Jordan	JO
Kazakhstan	KZ
Kenya	KE
Kiribati	KI
Korea, Democratic People's Republic (North)	KP
Korea, Republic of (South)	KR
Kosovo	KV
Kuwait	KW
Kyrgyzstan	KG
Laos	LA
Latvia	LV
Lebanon	LB
Lesotho	LS
Liberia	LR

Table 22 Category IV Country or Region and Territory Postal Systems

Country or Region	Code
Lithuania	LT
Libya	LY
Macau	MO
Macedonia	MK
Madagascar	MG
Malawi	MW
Malaysia	MY
Maldives	MV
Mali	ML
Malta	MT
Mauritania	MR
Mauritius	MU
Mexico	MX
Moldova	MD
Mongolia	MN
Montenegro	ME
Montserrat (UK)	MS
Morocco	MA
Mozambique	MZ
Myanmar	MM
Namibia	NA
Nauru	NR
Nepal	NP
Netherlands Antilles (NL)	AN
Nicaragua	NI
Niger	NE
Nigeria	NG
Niue	NU
Norfolk Island (AU)	NF
Oman	OM
Pakistan	PK
Panama	PA
Papua New Guinea	PG
Paraguay	PY
Peru	PE

Table 22 Category IV Country or Region and Territory Postal Systems

Country or Region	Code
Philippines	PH
Pitcairn Islands (UK)	PN
Qatar	QA
Romania	RO
Russia	RU
Rwanda	RW
Saint Helena (UK)	SH
Saint Kitts and Nevis	KN
Saint Lucia	LC
Saint Vincent and the Grenadines	VC
Samoa	WS
Sao Tome and Principe	ST
Saudi Arabia	SA
Senegal	SN
Serbia	RS
Seychelles	SC
Sierra Leone	SL
Singapore	SG
Slovakia	SK
Slovenia	SI
Solomon Islands	SB
Somalia	SO
South Georgia and the South Sandwich Islands (UK)	GS
Sri Lanka	LK
Sudan	SD
Suriname	SR
Swaziland	SZ
Syria	SY
Taiwan	TW
Tajikistan	TJ
Tanzania	TZ
Thailand	TH
Timor-Leste	TL
Togo	TG
Tokelau	TK

Table 22 Category IV Country or Region and Territory Postal Systems

Country or Region	Code
Tonga	TO
Trinidad and Tobago	TT
Tunisia	TN
Turkey	TR
Turkmenistan	TM
Turks and Caicos Islands (UK)	TC
Tuvalu	TV
Uganda	UG
Ukraine	UA
United Arab Emirates	AE
Uruguay	UY
Uzbekistan	UZ
Vanuatu	VU
Venezuela	VE
Vietnam	VN
Western Sahara	EH
Yemen	YE
Zambia	ZM
Zimbabwe	ZW

Restricted and Denied Parties List

Export Compliance uses the following government agency lists to screen order data. If you use Decision Manager, you can use these lists to create custom rules.



Important

To leverage any lists other than the default categories of OFAC and TEL, users must specify list categories when calling the service. When requesting a list category, all respective programs are reviewed.

Table 23 Restricted and Denied Parties List

List Category	Program Abbreviation	Name
AUSTRALIA	AUS_UNSC	Australia Department of Foreign Affairs and Trade (DFAT) United Nations Security Council (UNSC) Resolution
	AUS_ALQ	Australia DFAT UNSCR 1267 - Al Qaida and Taliban
	AUS_CAR	Australia DFAT UNSCR 2127 - Central Africa Republic
	AUS_IRN	Australia DFAT UNSCR 1737 - Iran
	AUS_IRQ	Australia DFAT UNSCR 1518 - Iraq
	AUS_AUTO_LIB	Australia Autonomous Sanctions Regulations 2011 - Libya
	AUS_AUTO_KOR	Australia Autonomous Sanctions Regulations 2011 - North Korea
	AUS_KOR	Australia DFAT UNSCR 1718 - North Korea
	AUS_SOM	Australia DFAT UNSCR 751 - Somalia
	AUS_SDT	Australia DFAT Foreign Affair
	AUS_SUD	Australia DFAT UNSCR 1591 - Sudan
	AUS_LBR	Australia DFAT UnSCR 1521 - Liberia
	AUS_UKR	Autonomous (Ukraine)
	AUS_AUTO_ZIM	Australia Autonomous Sanctions Regulations 2011 - Zimbabwe
BIS	BIS_DPL	BIS Denied Person List
	BIS_ENT	BIS Entity List
	BIS_UNV	BIS Unverified List

Table 23 Restricted and Denied Parties List (Continued)

List Category	Program Abbreviation	Name
CAN_CCTER	CAN_CCTER	Canada Criminal Code Terrorist Entities
CAN_FACFO	CAN_FACFO	Canada Freezing Assets of Corrupt Foreign Officials (FACFO) Act
CAN_JVCFO	CAN_JVCFO	Canada Justice for Victims of Corrupt Foreign Officials Regulations
CAN_SEMA	CAN_SEMA	Canada Special Economic Measures Act (SEMA)
CANADA_SC	CANADA_SC	Canada Sanctioned Countries List
DOS_CISADA	DOS_CISADA	Dept of State Comprehensive Iran Sanctions, Accountability and Divestment Act of 2010 (CISADA)
DOS_DTC	US_DEBARRED	Defense Trade Controls Debarred Parties List
DOS_ISN	ISN_ISNA	Iran Syria Non-Proliferation Act of 2005
	ISN_MSL	BIS Missile Sanctions Laws
	ISN_CBW	BIS Chemical and Biological Weapons Sanctions
	ISN_NPWMD	Nonproliferator Weapons of Mass Destruction
	ISN_LME	Sanctions for the Transfer of Lethal Military Equipment
	ISN_Iran_Iraq	Iran-Iraq Arms Nonproliferation Act of 1992
	ISN_INKSNA	Iran, North Korea, Syria Nonproliferation Act Sanctions
	ISN_INPA	Iran Nonproliferation Act of 2000
ENGLAND	HMTreasury	Her Majesty's Treasury (HM Treasury) Sanction List
	HMT_AFG	HM Treasury Afghanistan Sanction
	HMT_SYR	HM Treasury Syria Sanction
	HMT_BEL	HM Treasury Belarus Sanction
	HMT_CAF	HM Treasury Central African Republic Sanction
	HMT_CON	HM Treasury Congo Sanction
	HMT_EGY	HM Treasury Egypt Sanction
	HMT_IRN	HM Treasury Iran Sanction
	HMT_DPRK	HM Treasury North Korea Sanction
	HMT_GIN	HM Treasury Republic of Guinea Sanction
	HMT_GNB	HM Treasury Guinea-Bissau Sanction
	HMT_SOM	HM Treasury Somalia Sanction
	HMT_ALQ	HM Treasury Al-Qaida Sanction
	HMT_SUD	HM Treasury Sudan Sanction
	HMT_SDT	HM Treasury Terrorist Financing Sanction
	HMT_UKM	Ukraine (Misappropriation)

Table 23 Restricted and Denied Parties List (Continued)

List Category	Program Abbreviation	Name
	HMT_UKS	Ukraine (Sovereignty)
	HMT_YEM	Yemen
	HMT_ZIM	HM Treasury Zimbabwe Sanction
EUROPE	EUROPE	European Sanctions and Embargoes
FATF	FATF	Financial Action Task Force on Money Laundering
FBI	FBI_10MW	Federal Bureau of Investigation (FBI) Ten Most Wanted Fugitives List
	FBI_FGT	FBI Wanted Fugitives List
HMT_USTI	HMT_USL	HM Treasury Ukraine Sovereignty and Territorial Integrity (USTI) List
INTERPOL	INTERPOL	Recent Most Wanted List & Hague International Criminal Court
JAPAN	JAPAN	Japan Ministry of Economy, Trade and Industry (METI) Sanction List
OFAC	BALKANS	Balkans
	BELARUS	Belarus Executive Order and Designations
	BPI-PA	Blocked Pending Investigation - Patriot Act of 2001
	BPI-SDNT	Blocked Pending Investigation - SDNT
	BPI-SDNTK	Blocked Pending Investigation - SDNT Kingpin Act
	BURMA	Burma Sanctions
	JADE	Burma Junta's Anti-Democratic Efforts
	COTED	Côte d'Ivoire (Ivory Coast) Sanctions
	CUBA	Cuba Sanctions
	DRCONGO	Democratic Republic of the Congo
	FinCEN_311F	FinCEN 311 List - The Finding
	FinCEN_311R	FinCEN 311 List - The Final Rule
	FinCEN_311P	FinCEN 311 List - The Notice of Proposed Rulemaking
	FTO	Foreign Terrorist Organization
	IRAN	Iran
	IRAQ2	Iraq Sanctions - Blocking property of the former regimes - Exec 13315
	IRAQ3	Iraq Sanctions - Executive Order 13350
	LEBANON	Lebanon
	LIBERIA	Liberia
	LIBYA2	Libya Sanctions

Table 23 Restricted and Denied Parties List (Continued)

List Category	Program Abbreviation	Name
	NPWMD	Non-Proliferators Weapons of Mass Destruction
	NS-PLC	Non-SDN Palestinian Legislative Council
	DPRK	North Korea
	SOMALIA	Somalia Sanctions
	SDGT	Specially Designated Global Terrorist
	SDNT	Specially Designated Narcotics Traffickers
	SDNTK	Specially Designated Narcotics Traffickers - Kingpin Act
	SDT	Specially Designated Terrorist
	SUDAN	Sudan
	DARFUR	Sudan Darfur Region
	SYRIA	Syria
	TCO	Transnational Criminal Organizations
	WMD	Weapons of Mass Destruction Trade Control Regulations
	ZIMB	Zimbabwe
OFAC_SSI	UKRAINE-EO13662	OFAC Sectoral Sanctions Identifications List - UKRAINE Executive Order 13662
TEL	DOS_TEL	Terrorist Exclusion List
UNSL	UN_ALQ	UN Resolutions 1267 (1999) and 1989 (2011) concerning Al-Qaeda and associated individuals and entities
	UN_CAR	UN Resolution 2127 (2013) concerning Central African Republic
	UN_CON	UN Resolution 1533 (2004) concerning the Democratic Republic of the Congo
	UN_DPRK	UN Resolution 1718 (2006) concerning the Democratic People's Republic of Korea
	UN_GNB	UN Resolution 2048 (2012) concerning Guinea-Bissau
	UN_IRN	UN Resolution 1737 (2006) concerning the Islamic Republic of Iran
	UN_IRQ	UN Resolution 1518 (2003) concerning Iraq and Kuwait
	UN_IVO	UN SCR 1572 - Cote d'Ivoire
	UN_LBR	UN SCR 1521 - Liberia
	UN_LIB	UN Resolution 1970 (2011) concerning Libya
	UN_MLI	UN SCR 2374 - Mali

Table 23 Restricted and Denied Parties List (Continued)

List Category	Program Abbreviation	Name
	UN_SLE	UN SCR 1132 - Sierra Leone
	UN_SOM	United Nations Sanction List - Resolutions 751 (1992) and 1907 (2009) concerning Somalia and Eritrea
	UN_SOSUD	UN SCR 2206 - South Sudan
	UN_SUD	UN Resolution 1591 (2005) and 2206 (2015) concerning The Sudan
	UN_TAL	UN Resolution 1988 (2011) concerning All States - Taliban
	UN_YEM	UN Resolution 2140 (2014) concerning Yemen
WBNK	WBNK_DEBARRED	World Bank Listing of Ineligible Firms and Individuals

Address Type

The following address type codes are returned in the **davReply_addressType** reply field.

Table 24 Address Type Codes

Code	Description
F	Firm.
G	General delivery.
H	High-rise apartment or office building.
M	Military.
P	Post office box.
R	Rural route or highway contract.
S	Street (usually one side of one city block).
FD	Firm default. The standardization process was unable to assign a firm extended ZIP code.
GD	General delivery default. Assign when general delivery is the only primary name listed for the ZIP code.
HD	High-rise default. The standardization process assigned the extended ZIP code for the entire building. Assignment at the unit, floor, or wing level is possible. A suite or apartment number may be out of range.
RD	Rural route or highway contract default. The standardization process assigned the extended ZIP code for the entire route but was unable to assign the box number.
SD	Street default. The standardization process assigned the extended ZIP code for the block because no extended ZIP code for the building.
UD	Unique default. Either the owner of the ZIP code did not assign extended ZIP codes, or the address was not matched.